

Engine protection

Against overload and overvoltage by using a lockable motor circuit breaker. Management of limit switches while opening and closing action.

Easy and quick connecting

Every connection is done through connecting terminals or at the bottom of each element. Settled with input/output terminals (control and power) for an efficient connection.

Secure assembly

Settled with hinged lid, which enables a secure assembly and maintenance. Fully equipped with all the needful cable glands.

Bus 3 Wires: Switch box



Bus 3 Wires: Switch box

The switch box is responsible of protecting the system against overload and short circuit, to turn on the motor as well as responsible for the management of limit switches (if applicable).

The switch box performs a comprehensive and safe protection of the motor. Equipped with independent motor protection switch, it is designed to avoid any damage over the motor due to overload or overvoltage. Besides, the motor protection switch allows to perform safe maintenance work by activating the independent electrical locking in each motor.

The switch box deals also with the management of limit switches, located both on the motor or externally, if applicable. E.g.: in case of top vents ventilation motors.

- Protection of the motor through circuit breaker: overloads, overvoltage...
- Remote control from interface panel at 230 VAC or 24 VDC.
- Management of limit switches.
- User friendly and extremely sturdy unit.
- Wide range of intensities, in order to cover all kind of engines.

Technical Specifications

CODE CONFIGURATION

CP/3H/VOL/NM/PT/FC

VOLTAGE OF CONTROL BUS [VOL]	230 VAC	230
	24 VDC	024
SCHEME TYPE [NM]	Easy: on - off	01
	Double: open-close	02
INTENSITY RANGE IN AMPERES [PT]	0.35 - 0.5	01
	0.45 - 0.63	02
	0.7 - 1	03
	0.9 - 1.25	04
	1.4 - 2	05
	2.2 - 3.2	06
LIMIT SWITCH MANAGEMENT [FC]	Without management	00
	With management	01

E.G.

CP/3H/230/02/02/01



Switch Box for Bus 3 wires, control to 230 volts, double scheme (open/close), amperage between 0.45 A and 0.63 A and with management of limit switches.

TECHNICAL SPECIFICATIONS

Power supply: 230/400 VAC 50-60 Hz

Control supply: 24 VDC/230 VAC 50-60 Hz

Level of protection: IP 66 (Protection against powerful water jets)

Operation temperature: -25°C-60°C

Operation Humidity: 0-95%

Maximum altitude: 2.000 m